

*i-Line*TM

TECHNICAL SPECIFICATIONS

PRODUCT DESCRIPTION	Tufted Textured Loop Modular Carpet
YARN/FIBRE	STRUTTURA by Aquafil TM
MACHINE GAUGE	1/12 th gauge
PILE HEIGHT	3.0mm +/- 0.5mm
TOTAL THICKNESS	6.5mm +/- 0.5mm
TILE SIZE	500mm x 500mm
BACKING STRUCTURE	GlasBac®, GlasBac®RE and CushionBac TM available
LAYOUT OPTIONS	Quarter Turn and Brick
RECOMMENDED INSTALLATION METHODS	<ul style="list-style-type: none"> • Please refer to the instructions detailed with the InterfaceFLOR Installation Manual available at www.interfaceFLOR.com.au • TacTilesTM is the preferred installation method for both GlasBac® and GlasBac®RE carpet tiles • Inter-TacTM is a water based pressure sensitive adhesive especially manufactured for installation of InterfaceFLOR products
ACCREDITATION	All InterfaceFLOR modular carpet manufacturing facilities worldwide maintain registration to ISO 9001 Quality Management Systems and ISO 14001 Environmental Management Systems

PERFORMANCE SPECIFICATIONS

AREA OF USE	Commercial Extra Heavy Duty & Stairs
DIMENSIONAL STABILITY	Less than 0.2% variation
ANTI-STATIC	AATCC 134 < 3000 Volts
ANTIMICROBIAL	Intersept®
SOIL & STAIN PROTECTION	Protekt2®
WARRANTY	15 Year Limited Warranty – against manufacturing defects, electrostatic propensity, excessive wear, dimensional stability Castor Chair Warranty – 15 year available upon request

SUSTAINABILITY SPECIFICATIONS

LESS WASTE	Modular carpet creates about 80% less installation waste than broadloom
RECYCLABLE	GlasBac® and GlasBac®RE products qualify for recycling under InterfaceFLOR's optional ReEntry TM carpet reclamation program
RECYCLED CONTENT	Depending on backing selection this product has a total recycled content by weight up to 50%
ENVIRONMENTAL ACCREDITATION	100% Green Star Points

LIGHT REFLECTIVE VALUE

• Browse	0.15	• Network	0.17	• E-mail	0.36	• Password	0.32	• Favourites	0.45
• Search	0.15	• Login	0.16	• Username	0.18				

www.interfaceflor.com.au
1800 008 101