

# Blueprint™

## TECHNICAL SPECIFICATIONS

PRODUCT DESCRIPTION	Tufted Multi-Level Loop Pile Modular Carpet
YARN/FIBRE	Universal Optimum RE
MACHINE GAUGE	1/12 <sup>th</sup> gauge
PILE HEIGHT	4.0mm +/- 0.5mm
TOTAL THICKNESS	7.0mm +/- 0.5mm
TILE SIZE	500mm x 500mm
BACKING STRUCTURE	GlasBac®, GlasBac®RE and CushionBac™ available
LAYOUT OPTIONS	Quarter Turn, Ashlar, Brick
RECOMMENDED INSTALLATION METHODS	<ul style="list-style-type: none"> <li>• Please refer to the instructions detailed with the InterfaceFLOR Installation Manual available at <a href="http://www.interfaceFLOR.com.au">www.interfaceFLOR.com.au</a></li> <li>• TacTiles™ is the preferred installation method for both GlasBac® and GlasBac®RE carpet tiles</li> <li>• Inter-Tac™ is a water based pressure sensitive adhesive especially manufactured for installation of InterfaceFLOR products</li> </ul>
ACCREDITATION	All InterfaceFLOR modular carpet manufacturing facilities worldwide maintain registration to ISO 9001 Quality Management Systems and ISO 14001 Environmental Management Systems

## PERFORMANCE SPECIFICATIONS

AREA OF USE	Commercial Extra Heavy Duty & Stairs
DIMENSIONAL STABILITY	Less than 0.2% variation
ANTI-STATIC	AATCC 134 < 3000 Volts
ANTIMICROBIAL	Intersept®
SOIL & STAIN PROTECTION	Protekt2®
WARRANTY	15 Year Limited Warranty – against manufacturing defects, electrostatic propensity, excessive wear, dimensional stability Castor Chair Warranty – 15 year available upon request

## SUSTAINABILITY SPECIFICATIONS

LESS WASTE	Modular carpet creates about 80% less installation waste than broadloom
RECYCLABLE	GlasBac® and GlasBac®RE products qualify for recycling under InterfaceFLOR's optional ReEntry™ carpet reclamation program
RECYCLED CONTENT	Depending on backing selection this product has a total recycled content by weight up to 50%
ENVIRONMENTAL ACCREDITATION	100% Green Star Points

## LIGHT REFLECTIVE VALUE

• Contour	0.35	• Create	0.46	• Design	0.23	• Diagram	0.45	• Draft	0.14
• Draw	0.09	• Form	0.10	• Plot	0.17	• Sketch	0.44		